




43F-LCF78-ECO

4.3-10 Female Connector for 7/8" Coaxial Cable, ECO-Series

ECO Series connectors are designed for use with CELLFLEX® ECO cables.

Feature / Benefits

- Cost effective two-piece design for safe and easy installation
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 67 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



Technical features

GENERAL SPECIFICATIONS

Cable Size	7/8
Cable Type	LCF78-50JA-ECO; LCF78-50JFNA-ECO
Model Series	LCF78-50 Series
Connector Interface	4.3-10
Connector Type	ECO Series
Sealing Method	O-ring

TESTING AND ENVIRONMENTAL

Waterproof Level	IP67
------------------	------

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	Trimetal/Silver
Length	57mm (2.244in)
Outer Diameter	36.5mm (1.437in)
Inner Contact Attachment	Spring Finger
Outer Contact Attachment	Spring Finger

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms	
3rd Order IM Product @ 2x20 Watts	-155	
Maximum Frequency	5 GHz	
Frequency Range	VSWR value	Return Loss value
DC < f ≤ 1000MHz	1.1	26.4
1700 < f ≤ 2700MHz	1.13	24.3
2700 < f ≤ 3000MHz	1.15	23.1
3000 < f ≤ 5000MHz	1.3	17.7

External Document Links

Notes



**43F-LCF78-ECO**

4.3-10 Female Connector for 7/8" Coaxial Cable, ECO-Series

**Related Documents**



**TML Value Proposition**

Value Propositions