

Coaxial Adapter, 4.3-10 Female / N Female

Technical features

STRUCTURE

Product Line	Coaxial Cable Components
Product Type	Coaxial Adapter
Coaxial Cable Type	Foam Dielectric, Ultraflexible Foam Dielectric, Radiating Cable

MECHANICAL SPECIFICATIONS

Connector A	4.3-10 Female
Center Contact Connector A	Spring Bronze, Silver plated
Outer Contact Connector A	Brass, CuSnZn plated
Connector B	N Female
Center Contact Connector B	Spring Bronze, Silver plated
Outer Contact Connector B	Brass, CuSnZn plated
Dielectric	PTFE
Sealing class	IP68, connected

ELECTRICAL SPECIFICATIONS

Frequency Range - MHz	DC - 6000
VSWR	0-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44
Insertion Loss	0.1
3rd Order IM Product @ 2x20 Watts	-163 dBc
Power Rating	0.5

TEMPERATURE SPECIFICATIONS

Operation Temperature -45 to 85 (-49 to 185)
--

PACKAGING INFORMATION

l	Package Quantity	1
ı		

External Document Links Notes

43F-NF REV : D REV DATE : 15 Nov 2025 **www.rfsworld.com**