

The P02 premium performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to RADIAFLEX® cables. The connectors should provide outstanding value to users because they permit quick, easy and reliable installation at any location, thereby allowing the operator flexibility while saving installation time and money.

Feature / Benefits

- Designed for Fast and Easy Installation Reliable and simple attachment avoids unnecessary 197 connector adjustments and provides
- Outstanding performance. Saves time and provides cost savings
- Robust Mechanical Design Best in class PIM performance
- Excellent Electrical Performance Low VSWR
- Totally Waterproof Assures safe, long term operation in the harshest of environments.
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Cable Size	1/2	
Cable Type	Radiating	
Model Series	all ALF and RLK-Series	
Connector Interface	4.3-10	
Connector Type	Straight	
Sealing Method	Shrinking Sleeve	

TESTING AND ENVIRONMENTAL

Waterproof Level	IP68	
Installation Temperature	-25°C to 60°C (-13°F to 140°F)	
Storage Temperature	-70°C to 85°C (-94°F to 185°F)	
Operation Temperature	-40°C to 85°C (-40°F to 185°F)	

MECHANICAL SPECIFICATIONS

Body Material	Brass / Plating: Tri Metal	
Inner Contact Material	Copper / Plating: Silver	
Length	85.8mm (3.38in)	
Outer Diameter	26mm (1.02in)	
Inner Contact Attachment	Spring Finger / Plating: Silver	
Outer Contact Attachment	Spring Loop / Plating: Silver	

43F-RA12-P02 REV : B REV DATE : 11 Dec 2025 **www.rfsworld.com**

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms		
3rd Order IM Product @ 2x20 Watts	-155 / -160 (typ.)		
Maximum Frequency	6 GHz		
Frequency Range	VSWR value	Return Loss value	
0.0 - 1.0 GHz	1.03	36.6	
>1.0 - 2.0 GHz	1.06	30.7	
>2.0 - 3.0 GHz	1.08	28.3	
>3.0 - 4.0 GHz	1.11	25.7	
>4.0 - 6.0 GHz	1.15	23.1	

ACCESSORIES

Trimming Tool	TRIM-SET-R12-P02

External Document Links

Notes

• In order to achieve the PIM specs. the use of the trimming tool is mandatory.

43F-RA12-P02 REV : B REV DATE : 11 Dec 2025 **www.rfsworld.com**