

**43M-LCF78-E01****4.3-10 Male Straight Connector for 7/8" Coaxial Cable, OMNI FIT™ Premium, O-Ring and compression sealing**

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 4.3-10 connector is an innovative, space-saving RF connection meeting all requirements even under the most severe environmental conditions and not relying on coupling nut torque. Sealing against outer conductor and jacket by means of O-Ring and 360° compression fit.

Feature / Benefits

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Tri metal alloy plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features**GENERAL SPECIFICATIONS**

Cable Size	7/8
Cable Type	Foam Dielectric
Model Series	LCF78-50 Series, RCF78-50 Series
Connector Interface	4.3-10
Connector Type	OMNI FIT™ PREMIUM Straight
Sealing Method	Sealing rubber + 360° clamping

TESTING AND ENVIRONMENTAL

Waterproof Level	IP68
------------------	------

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	NiTin/Silver
Length	74mm (2.91in)
Outer Diameter	37mm (1.46in)
Inner Contact Attachment	Spring finger
Outer Contact Attachment	360° clamping



43M-LCF78-E01

4.3-10 Male Straight Connector for 7/8" Coaxial Cable, OMNI FIT™ Premium, O-Ring and compression sealing

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms	
3rd Order IM Product @ 2x20 Watts	-163 ; typical -167	
Maximum Frequency	6 GHz	
Frequency Range	VSWR value	Return Loss value
0 < f ≤ 1.0 GHz	1.02	40
1.0 < f ≤ 2.2 GHz	1.03	37
2.2 < f ≤ 2.7 GHz	1.03	36
2.7 < f ≤ 3.8 GHz	1.06	31
3.8 < f ≤ 5.0 GHz	1.11	26
5.0 < f ≤ 6.0 GHz	1.15	23

ACCESSORIES

Trimming Tool	TRIM-SET-L78-D01, TRIM-LCF78-D01-A
---------------	------------------------------------

External Document Links

Notes