4.3-10 Male Connector for 1/2" Coaxial SuperFlexibleCable, OMNI FIT™ standard



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications. The 4.3-10 connector is an innovative, space-saving RF connection meeting all requirements even under the most severe environmental conditions and not relying on coupling nut torque to meet PIM performance.

Feature / Benefits

- Cost effective two-piece design for safe and easy installation
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up, reduces the number of dropped calls and avoids revenue losses
- Standard electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Cable Size	1/2		
Cable Type	Foam Dielectric Superflexible		
Model Series	SCF12-50 Series		
Connector Interface	4.3-10		
Connector Type	OMNI FIT™ Standard		
Sealing Method	O-ring		

TESTING AND ENVIRONMENTAL

Waterproof Level IP68	
-----------------------	--

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	Trimetal/Silver	
Length	43.9mm (1.73in)	
Outer Diameter	25mm (1in)	
Inner Contact Attachment	Basket	
Outer Contact Attachment	Rigidity impaction	

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms		
3rd Order IM Product @ 2x20 Watts	-162 ; typical -166		
Maximum Frequency	6 GHz		
Frequency Range	VSWR value	Return Loss value	
0 < f ≤ 1.0 GHz	1.03	36.6	
1.0 < f ≤ 2.7 GHz	1.04	34.1	
2.7 < f ≤ 3.7 GHz	1.08	28.3	
3.7 < f ≤ 5.0 GHz	1.1	26.4	
5.0 < f ≤ 6.0 GHz	1.25	19.1	

43M-SCF12-C03 REV : B REV DATE : 11 Dec 2025 www.rfsworld.com

Trimming Tool	TRIM-SET-S12-C02	
Trimming 1001	1 KIIVI-5E I -51 Z-CUZ	
External Document Links	Notes	

43M-SCF12-C03 REV : B REV DATE : 11 Dec 2025 www.rfsworld.com