
43MR-LCF12-ECO_PRELIMINARY_Forstar

4.3-10 Male Right Angle Connector for 1/2" Coaxial Cable, ECO-Series



ECO Series connectors are designed for use with CELLFLEX® cables.

Feature / Benefits

- Cost effective two-piece design for safe and easy installation
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 67 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Cable Size	1/2	
Cable Type	Foam Dielectric	
Model Series	LCF12-50 Series	
Connector Interface	4.3-10	
Connector Type	ECO Series	
Sealing Method	O-ring	

TESTING AND ENVIRONMENTAL

Waterproof Level IP67	
-----------------------	--

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	Trimetal/Silver	
Length	57mm (2.244in)	
Outer Diameter	35mm (1.378in)	
Inner Contact Attachment	Spring Finger	
Outer Contact Attachment	Spring Finger	

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms		
3rd Order IM Product @ 2x20 Watts	-155		
Maximum Frequency	6 GHz		
Frequency Range	VSWR value	Return Loss value	
DC < f ≤ 1000MHz	1.1	26.44	
1000 < f ≤ 2700MHz	1.15	23.12	
2700 < f ≤ 3000MHz	1.2	20.82	
3000 < f ≤ 5800MHz	1.4	15.56	

External Document Links Notes

43MR-LCF12-ECO_PRELIMINARY_Forstar

REV: A

REV DATE: 15 Nov 2025

www.rfsworld.com

Related Documents TML Value Proposition Value Propositions

43MR-LCF12-ECO_PRELIMINARY_Forstar

REV : A REV DATE : 15 Nov 2025 www.rfsworld.com