



716M-SCF14-E01

7-16 DIN Male Connector for 1/4" Coaxial Cable, OMNI FIT™ Premium, Straight, O-Ring and 360° compression sealing



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications. The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions. Sealing against outer conductor and jacket by means of o-ring and 360° compression fit.

Feature / Benefits

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Tri metal alloy plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Cable Size	1/4
Cable Type	Foam Dielectric Superflexible
Model Series	SCF14-50 Series
Connector Interface	7-16 DIN
Connector Type	OMNI FIT™ PREMIUM Straight
Sealing Method	O-ring + 360° Compression

TESTING AND ENVIRONMENTAL

Waterproof Level	IP68
------------------	------

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	Tri metal alloy / Silver
Length	55mm (2.165in)
Outer Diameter	20mm (0.787in)
Inner Contact Attachment	Spring Finger
Outer Contact Attachment	360° clamping



716M-SCF14-E01


7-16 DIN Male Connector for 1/4" Coaxial Cable, OMNI FIT™ Premium, Straight, O-Ring and 360° compression sealing

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms	
3rd Order IM Product @ 2x20 Watts	-163 ; typical -167	
Maximum Frequency	6 GHz	
Frequency Range	VSWR value	Return Loss value
0 < f ≤ 1.0 GHz	1.03	37
1.0 < f ≤ 2.2 GHz	1.06	31
2.2 < f ≤ 2.7 GHz	1.08	28
2.7 < f ≤ 3.8 GHz	1.12	25
3.8 < f ≤ 5.0 GHz	1.17	22
5.0 < f ≤ 6.0 GHz	1.22	20

ACCESSORIES

Trimming Tool	TRIM-SCF14-D01-A
---------------	------------------



External Document Links

Notes