



B220-185FP

Connector for FLEXWELL® elliptical waveguide E185, PBR220 Flange



Standard connector for FLEXWELL® elliptical waveguide E185 with PBR220 flange, Plast 2000 sealed
frequency range: 17.7 - 19.7 GHz

Feature / Benefits

Superior Design

- Due to the precise manufacturing no tuning screws are necessary
- The terminations are brass passivated for good electrical performance
- A gas inlet is included
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Quick & Easy Installation

- Different flaring tools are available
- No tuning in the field

Technical features

STRUCTURE

Transmission Line Type	Elliptical Waveguide
Cable Type	E185
Model Series	E185 Series
Connector Frequency Range	17.7 - 19.7
Connector Type	Fixed
Sealing Method	Plast 2000
Plating Outer/Inner	Brass
Waterproof Level	IP68
Gas Inlet	G 1/8
Connector Interface	PBR220

MECHANICAL SPECIFICATIONS

Length	90mm (3.6in)
Outer Diameter	40mm (1.6in)
Weight	0.4kg (0.88lb)
Sealing Volume	20cm ³ (0.68ounces)

External Document Links

Notes
Sealing component PLAST 2000 is **not** part of the connector delivery and must be ordered separately.