

4" Feed Through Boot Assembly Hole for E100/E105 Waveguide

Feature / Benefits

These innovative boot assemblies feature a one-piece design which reduces installation time. The split, one-piece style simplifies clamping and frees the installers hands to position the cable runs. Boot assemblies are designed to be fitted onto 4" entry panels in wall/roof feed-through applications. The durable boot is designed to meet ASTM-D2000 and SAE J200 specifications. Each boot assembly includes the boot, two round member adapter clamps which fit inside the boot assembly to hold the waveguide in place.

Technical features

STRUCTURE

Ш	Product Type	Wall/Roof Feed-Through System
---	--------------	-------------------------------

MECHANICAL SPECIFICATIONS

Material	FPDM rubber
Material	LF DIVITUDDET

TEMPERATURE SPECIFICATIONS

Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Storage Temperature	-50°C to 85°C (-58°F to 185°F)

PACKAGING INFORMATION

Package Quantity	1
Weight per piece	0.7kg (1.6lb)
Box Dimensions (Bulk Shipping)	635 x 330 x 178 (25 x 13 x 7) L x W x H

External Document Links Notes

BOOT4-105 REV : A REV DATE : 15 Nov 2025 **www.rfsworld.com**