Cable hanger, non-insulated, bolt-on, for 1 1/4" coaxial cable and eliptical waveguide E65 and E70



Hanger, non-insulated, bolt-on for coaxial cable LCF114 / LCFS114 / RCF114 and for eliptical waveguide E65/EP65 and E70/EP70 made of stainless steel

Feature / Benefits

Stainless steel hangers for supporting elliptical waveguide or coaxial cable to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot

Technical features

GENERAL SPECIFICATIONS

Product Type	Hanger
Hanger Type	Bolt-On, non-insulated
Cable Type	Coaxial Foam Dielectric, Radiating Cable, Hybrid

TESTING AND ENVIRONMENTAL

Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Storage Temperature	-50°C to 85°C (-58°F to 185°F)

MECHANICAL SPECIFICATIONS

Cable Size	1-1/4"
Number of Cable / Waveguide Runs	1
Material	Stainless Steel

PACKAGING INFORMATION

Package Quantity	10
------------------	----

External Document Links

Notes

CLAMP-114REV : BREV DATE : 15 Nov 2025www.rfsworld.com