



LCF78-50CPR

7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

CELLFLEX®7/8" premium attenuation low loss flexible cable



Feature / Benefits

- **Low Attenuation**
The low attenuation of CELLFLEX® coaxial cable results in highly efficient signal transfer in your RF system.
- **Complete Shielding**
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical features

APPLICATIONS

Applications	Indoor	Wireless Communication	TV & Radio	HF Defense	Microwave	Mobile Radio	Cable Solutions
--------------	--------	------------------------	------------	------------	-----------	--------------	-----------------

STRUCTURE

Cable Type	Foam-Dielectric, Corrugated
Size	7/8
Jacket Option	Black
Inner Conductor Diameter	9mm (0in)
Inner Conductor Material	Copper Tube
Dielectric Diameter	22mm (1in)
Dielectric Material	Foam Polyethylene
Outer Conductor Diameter	25mm (1in)
Outer Conductor Material	Corrugated Copper
Jacket Diameter	28mm (1in)
Jacket Material	Polyethylene, PE, Metalhydroxite Filling

TESTING AND ENVIRONMENTAL

Fire Performance	Flame Retardant, LS0H
Flame Retardant Jacket Specifications	Meets/Exceeds: IEC 60754-1, -2; IEC 60332-1, -3.C; UL 1581; UL 1666; NEC type CATVR; CPR: https://products.rfsworld.com/userfiles/cpr/rfs-products-cpr-compliance.pdf
Installation Temperature	-15°C to 60°C (5°F to 140°F)
Storage Temperature	-70°C to 85°C (-94°F to 185°F)
Operation Temperature	-50°C to 85°C (-58°F to 185°F)



LCF78-50CPR

7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

ELECTRICAL SPECIFICATIONS

Impedance	50 +/- 1 Ω
Maximum Frequency	5 GHz
Velocity	90 %
Capacitance	74pF/m (22.5pF/ft)
Inductance	0.185μH/m (0.056μH/ft)
Peak Power Rating	85 kW
RF Peak Voltage	2920 Volts
Jacket Spark	8000 Volt RMS
Inner Conductor dc Resistance	1.77ohm/1000 m (0.54ohm/1000 ft)
Outer Conductor dc Resistance	1.93ohm/1000 m (0.59ohm/1000 ft)
Return Loss (VSWR) Performance	Standard for 40-5000 MHz, Premium according to B-Class
Phase Stabilized	Phase stabilized and phase matched cables and assemblies are available upon request.

MECHANICAL SPECIFICATIONS

Cable Weight	0.45kg/m (0.3lb/ft)
Minimum Bending Radius	120mm (5in)
Minimum Bending Radius	250mm (10in)
Bending Moment	16 (12)
Tensile Strength	1440N (324lb)
Recommended / Maximum Clamp Spacing	0.8 / 1 (2.75 / 3.25)

**LCF78-50CPR**

7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.08	0.024	91
1	0.113	0.034	74.2
1.5	0.138	0.042	60.7
2	0.16	0.049	52.4
10	0.359	0.109	23.3
20	0.51	0.156	16.4
30	0.627	0.191	13.4
50	0.813	0.248	10.3
88	1.09	0.331	7.69
100	1.16	0.354	7.22
108	1.21	0.368	6.93
150	1.43	0.437	5.86
174	1.55	0.472	5.41
200	1.66	0.507	5.05
300	2.06	0.627	4.07
400	2.4	0.731	3.49
450	2.55	0.778	3.29
500	2.7	0.823	3.1
512	2.73	0.833	3.07
600	2.98	0.907	2.81
700	3.23	0.986	2.59
750	3.36	1.02	2.49
800	3.48	1.06	2.41
824	3.53	1.08	2.37
894	3.69	1.13	2.27
900	3.71	1.13	2.26
925	3.76	1.15	2.23
960	3.84	1.17	2.18
1000	3.93	1.2	2.13
1250	4.44	1.35	1.89
1400	4.73	1.44	1.77
1500	4.91	1.5	1.71
1700	5.27	1.61	1.59
1800	5.44	1.66	1.54
2000	5.77	1.76	1.45
2100	5.93	1.81	1.41
2200	6.09	1.86	1.38
2400	6.4	1.95	1.31
2500	6.55	2	1.28
2600	6.7	2.04	1.25
2700	6.84	2.09	1.23
3000	7.27	2.22	1.15
3500	7.95	2.42	1.05



LCF78-50CPR

7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

4000	8.6	2.62	0.974
4900	9.69	2.95	0.865
5000	9.81	2.99	0.854

External Document Links

Notes

Related Documents



Web URL to CPR resources with DoP and CE-label download folders

Other Documents