



**LCF78-50JA nicolas**  
7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable



CELLFLEX® 7/8" low loss flexible cable

**Feature / Benefits**

- Ultra Low Attenuation**  
The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- Complete Shielding**  
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- Low VSWR**  
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- Outstanding Intermodulation Performance**  
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- High Power Rating**  
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- Wide Range of Application**  
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects

**Technical features**

**APPLICATIONS**

Applications	Main feed line, intended for outdoor usage
--------------	--

**STRUCTURE**

Cable Type	Foam-Dielectric, Corrugated
Size	7/8
Jacket Option	Black
Inner Conductor Diameter	9.1mm (0.358in)
Inner Conductor Material	Copper Tube
Dielectric Diameter	21.5mm (0.846in)
Dielectric Material	Foam Polyethylene
Outer Conductor Diameter	25.2mm (0.992in)
Outer Conductor Material	Corrugated Copper
Jacket Diameter	27.8mm (1.094in)
Jacket Material	Black Polyethylene

**LCF78-50JA nicolas**

7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

**TESTING AND ENVIRONMENTAL**

Installation Temperature	-40°C to 60°C (-40°F to 140°F)
Storage Temperature	-70°C to 85°C (-94°F to 185°F)
Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Compliance	DIN EN ISO 9001:2015 ISO 14001:2015 RoHS 2011/65/EU - China RoHS SJ/T 11364-2006 REACH (EC 1907/2006) UL1581 - UV Resistance Jacket IEC 60754-1/-2

**ELECTRICAL SPECIFICATIONS**

Impedance	50 +/- 1 $\Omega$
Maximum Frequency	5 GHz
Velocity	88 %
Capacitance	74pF/m (22.5pF/ft)
Inductance	0.185 $\mu$ H/m (0.056 $\mu$ H/ft)
Peak Power Rating	85 kW
RF Peak Voltage	2920 Volts
Jacket Spark	8000 Volt RMS
Inner Conductor dc Resistance	2.04ohm/1000 m (0.62ohm/1000 ft)
Outer Conductor dc Resistance	1.55ohm/1000 m (0.472ohm/1000 ft)
Return Loss (VSWR) Performance	Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies
Phase Stabilized	Phase stabilized and phase matched cables and assemblies are available upon request.

**MECHANICAL SPECIFICATIONS**

Cable Weight	0.39kg/m (0.262lb/ft)
Minimum Bending Radius	120mm (5in)
Minimum Bending Radius	250mm (10in)
Bending Moment	13 (10)
Tensile Strength	1440N (324lb)
Recommended / Maximum Clamp Spacing	0.8 / 1 (2.75 / 3.25)



**LCF78-50JA nicolas**  
7/8" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

**ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)**

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
1	0.11	0.03	87,96
100	1.17	0.36	8.5
200	1.68	0.51	5.92
450	2.58	0.79	3.85
700	3.28	1.00	3.03
800	3.53	1.08	2.82
900	3.76	1.15	2.64
1800	5.55	1.70	1.79
2000	5.89	1.80	1.69
2200	6.23	1.90	1.60
2400	6.55	2.0	1.52
2700	7.01	2.14	1.42
3000	7.46	2.28	1.33
3500	8.17	2.49	1.22
4000	8.84	2.70	1.12
5000	10.11	3.09	0.98

External Document Links  
[CELLFLEX Drum Selection Guide](#)

Notes

**NOTES**

- Notes LCF78-50JTC: TC cables (temperature cycled) are cables that are aged in order to reduce hysteresis effects. Available upon request.
- Europe ordering code:
  - LCF78-50JA-1-50: LCF78-50J, 50m length, Carton
  - LCF78-50JA-1-250: LCF78-50J, 250m length, Drum 11-077-X
  - LCF78-50JA-1-500: LCF78-50J, 500m length, Drum 11-077-X
  - LCF78-50JA-3-500: LCF78-50J, CoO China, 500m length, Drum standard