



LCF78-50JL
7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable



CELLFLEX® Lite 7/8" low loss flexible cable

Feature / Benefits

- **Ultra Low Attenuation**
The further reduced attenuation of CELLFLEX® premium attenuation coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- **Complete Shielding**
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical features

APPLICATIONS

Applications	Main feed line, intended for outdoor usage
--------------	--

STRUCTURE

Cable Type	Foam-Dielectric, Corrugated
Size	7/8
Jacket Option	Black
Inner Conductor Diameter	9.1mm (0.358in)
Inner Conductor Material	Copper Tube
Dielectric Diameter	21.5mm (0.846in)
Dielectric Material	Foam Polyethylene
Outer Conductor Diameter	25.2mm (0.992in)
Outer Conductor Material	Corrugated Aluminium
Jacket Diameter	27.8mm (1.094in)
Jacket Material	Polyethylene, PE

TESTING AND ENVIRONMENTAL

Fire Performance	Halogene Free
Installation Temperature	-40°C to 60°C (-40°F to 140°F)
Storage Temperature	-70°C to 85°C (-94°F to 185°F)
Operation Temperature	-50°C to 85°C (-58°F to 185°F)



LCF78-50JL
7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

ELECTRICAL SPECIFICATIONS

Impedance	50 +/- 1 Ω
Maximum Frequency	5 GHz
Velocity	88 %
Capacitance	75pF/m (22.9pF/ft)
Inductance	0.188μH/m (0.057μH/ft)
Peak Power Rating	85 kW
RF Peak Voltage	2920 Volts
Jacket Spark	8000 Volt RMS
Inner Conductor dc Resistance	2.05ohm/1000 m (0.62ohm/1000 ft)
Outer Conductor dc Resistance	1.6ohm/1000 m (0.48ohm/1000 ft)
Return Loss (VSWR) Performance	Standard (for 40-2700, 3300-4200, 4400-5000 MHz) or Premium
Phase Stabilized	Phase stabilized and phase matched cables and assemblies are available upon request.

MECHANICAL SPECIFICATIONS

Cable Weight	0.31kg/m (0.2lb/ft)
Minimum Bending Radius	120mm (5in)
Minimum Bending Radius	250mm (10in)
Bending Moment	13 (10)
Tensile Strength	1440N (324lb)
Recommended / Maximum Clamp Spacing	0.8 / 1 (2.75 / 3.25)

**LCF78-50JL**

7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.087	0.027	85
1	0.123	0.038	85
1.5	0.151	0.046	70.2
2	0.175	0.053	60.6
10	0.392	0.119	27
20	0.556	0.17	19.1
30	0.683	0.208	15.5
50	0.885	0.27	12
88	1.18	0.36	8.98
100	1.26	0.384	8.41
108	1.31	0.4	8.09
150	1.55	0.473	6.84
174	1.67	0.51	6.35
200	1.8	0.549	5.89
300	2.22	0.677	4.77
400	2.58	0.786	4.11
450	2.74	0.837	3.87
500	2.9	0.884	3.66
512	2.94	0.895	3.61
600	3.19	0.973	3.32
700	3.46	1.06	3.06
750	3.59	1.1	2.95
800	3.72	1.13	2.85
824	3.78	1.15	2.8
894	3.95	1.2	2.68
900	3.96	1.21	2.68
925	4.02	1.22	2.64
960	4.1	1.25	2.59
1000	4.19	1.28	2.53
1250	4.72	1.44	2.25
1400	5.02	1.53	2.11
1500	5.21	1.59	2.03
1700	5.58	1.7	1.9
1800	5.76	1.76	1.84
2000	6.1	1.86	1.74
2100	6.27	1.91	1.69
2200	6.43	1.96	1.65
2400	6.75	2.06	1.57
2500	6.9	2.1	1.54
2600	7.05	2.15	1.5
2700	7.2	2.2	1.47
3000	7.64	2.33	1.39
3500	8.33	2.54	1.27



7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

4000	8.98	2.74	1.18
4900	10.1	3.07	1.05
5000	10.2	3.11	1.04

External Document Links

Notes