

**LCFS114-50JFNB****1-1/4" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable**

CELLFLEX®1-1/4" premium attenuation low loss flexible cable

Feature / Benefits

- **Ultra Low Attenuation**
The further reduced attenuation of CELLFLEX® premium attenuation coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- **Complete Shielding**
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical features**APPLICATIONS**

Applications	Main feed line, intended for indoor usage
--------------	---

STRUCTURE

Cable Type	Foam-Dielectric, Corrugated
Size	1-1/4
Jacket Option	Black
Inner Conductor Diameter	13.1mm (0.52in)
Inner Conductor Material	Copper Tube
Dielectric Diameter	33mm (1.299in)
Dielectric Material	Foam Polyethylene
Outer Conductor Diameter	35.8mm (1.409in)
Outer Conductor Material	Corrugated Copper
Jacket Diameter	39mm (1.54in)
Jacket Material	Polyethylene, PE, Metalhydroxite Filling

TESTING AND ENVIRONMENTAL

Fire Performance	Flame Retardant, LSZH
Flame Retardant Jacket Specifications	Meets/Exceeds: IEC 60754-1, -2; IEC 60332-1-1, -2; IEC 61034-1, -2; IEC 60332-3-24 (formerly IEC 60332-3-C);
Installation Temperature	-25°C to 60°C (-13°F to 140°F)
Storage Temperature	-70°C to 85°C (-94°F to 185°F)
Operation Temperature	-50°C to 85°C (-58°F to 185°F)

**LCFS114-50JFNB**

1-1/4" CELLFLEX® Premium Attenuation Low-Loss Foam-Dielectric Coaxial Cable

ELECTRICAL SPECIFICATIONS

Impedance	50 +/- 1 Ω
Maximum Frequency	3.7 GHz
Velocity	88 %
Capacitance	73pF/m (22.9pF/ft)
Inductance	0.18 μ H/m (0.057 μ H/ft)
Peak Power Rating	176 kW
RF Peak Voltage	4200 Volts
Jacket Spark	10000 Volt RMS
Inner Conductor dc Resistance	1.5ohm/1000 m (0.45ohm/1000 ft)
Outer Conductor dc Resistance	1.2ohm/1000 m (0.36ohm/1000 ft)
Return Loss (VSWR) Performance	Standard for 320~480MHz, 820MHz~960MHz, 1700MHz~1880MHz, 1880MHz~2180MHz, 2300MHz~2500MHz, 2500MHz~2700MHz, 3000MHz~3600MHz

MECHANICAL SPECIFICATIONS

Cable Weight	0.777kg/m (0.522lb/ft)
Minimum Bending Radius	200mm (8in)
Minimum Bending Radius	380mm (15in)
Bending Moment	43 (32)
Tensile Strength	2490N (560lb)
Recommended / Maximum Clamp Spacing	1 / 1.2 (3.25 / 4)

ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
200	1.14	0.347	8.5
450	1.81	0.55	5.4
800	2.48	0.756	3.9
900	2.67	0.814	3.7
1800	4	1.22	2.4
2000	4.29	1.31	2.3
2200	4.48	1.36	2.2
2500	4.95	1.51	1.9
2700	5.24	1.6	1.9
3000	5.62	1.71	1.8
3400	6.1	1.86	1.7
3600	6.35	1.93	1.8

External Document Links

Notes