

Feature / Benefits

- Designed to precisely fit the cable diameter
- All double clamps externally interlock with single and 4 way clamps
- Manufactured in high grade polypropylene UV stabilised
- Also available in Low smoke Halogene material (LSZH)

Technical features

GENERAL SPECIFICATIONS

Product Type	Hanger					
Hanger Type	Double Clamp Hanger					
Cable Type	Power Cable, Hybrid Cable					


TESTING AND ENVIRONMENTAL


Operation Temperature	-40°C to 85°C (-40°F to 185°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)

MECHANICAL SPECIFICATIONS

Cable Size	5/8"
Number of Cable / Waveguide Runs	2
Material	polypropylene

MBH-BT10DREV : AREV DATE : 15 Nov 2025www.rfsworld.com







All dimensions are in mm; tolerances according to ISO 2768 m-H

Part Number	Cable Size	Colour	Α	В	С	D	Weight	Pack Qty	Box Qty
DW4	2 x 5/8"	Black	21	44	33	76	0.05	20	400

MBH-BT10DREV : AREV DATE : 15 Nov 2025www.rfsworld.com





All dimensions are in mm; tolerances according to ISO 2768 m-H

Part Number	Cable Size	Colour	Α	В	С	D	Weight	Pack Qty	Box Qty
DW4	2 x 5/8"	Black	21	44	33	76	0.05	20	400

External Document Links

Notes

Related Documents



TML Value Proposition Value Propositions

MBH-BT10DREV : AREV DATE : 15 Nov 2025www.rfsworld.com