

Single Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds one run of coax, allowing a compact bundle of up to 3x runs to be supported by stacking three blocks.

Feature / Benefits

- Single Multi Blocks are manufactured of polypropylene providing thermal, chemical and UV resistance in all
 environments.
- They come including angle member adapter and necessary hardware.
- The angle member adapter includes a tower member set screw.
- The hanger mounting rod may be located in either of two mounting holes, depending on orientation of the fixing member.
- Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.

Technical features

GENERAL SPECIFICATIONS

Product Type	Hanger
Hanger Type	Single Multi-block
Cable Type	Coaxial Foam Dielectric, Hybrid
Color	Black

TESTING AND ENVIRONMENTAL

Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Storage Temperature	-50°C to 85°C (-58°F to 185°F)


MECHANICAL SPECIFICATIONS

Cable Size	1-1/4
Number of Cable / Waveguide Runs	1 per layer, 1 layer, 1 run
Configuration	incl. Angle member adapter
Material	Metal part: Stainless steel Plastic parts: Polypropylene
Angle member adapter clamping range mm (in)	4 / 24 (0.157 / 0.945)
Angle member adpter threads	2x M8
Recommended / Maximum Clamp Spacing	1 / 1.2 (3.25 / 4)

PACKAGING INFORMATION

Package Quantity	10
Weight per piece	0.31kg (0.68lb)
Weight per kit	3.3kg (7.27lb)

MBHS114-1-F REV : E REV DATE : 15 Nov 2025 **www.rfsworld.com**



Notes

MBHS114-1-F REV: E REV DATE: 15 Nov 2025 www.rfsworld.com