N Female Connector for 7/8" Coaxial Cable, OMNI FIT™ standard, O-ring sealing



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

Feature / Benefits

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Cable Size	7/8	
Cable Type	Foam Dielectric	
Model Series	LCF78-50 Series	RCF78-50 Series
Connector Interface	N	
Connector Type	OMNI FIT™ Standard	
Sealing Method	O-ring	

TESTING AND ENVIRONMENTAL

Waterproof Level	IP68

MECHANICAL SPECIFICATIONS


Plating Outer/Inner	Trimetal/Silver	
Length	56.9mm (2.24in)	
Outer Diameter	35.5mm (1.4in)	
Inner Contact Attachment	Spring Finger	
Outer Contact Attachment	Spring C-Ring	

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms	
3rd Order IM Product @ 2x20 Watts	-157 ; typical -160	
Maximum Frequency	6 GHz	
Frequency Range	VSWR value	Return Loss value
0 < f ≤ 1.0 GHz	1.03	36.6
1.0 < f ≤ 2.7 GHz	1.04	34.1
2.7 < f ≤ 3.7 GHz	1.08	28.3
3.7 < f ≤ 5.0 GHz	1.15	23.1
5.0 < f ≤ 6.0 GHz	1.25	19.1

NF-LCF78-C03 REV : C REV DATE : 15 Nov 2025 www.rfsworld.com

N Female Connector for 7/8" Coaxial Cable, OMNI FIT™ standard, O-ring sealing



NF-LCF78-C03 REV : C REV DATE : 15 Nov 2025 **www.rfsworld.com**