

ECO Series connectors are designed for use with CELLFLEX® cables.

Feature / Benefits

- Cost effective two-piece design for safe and easy installation
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 67 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Cable Size	7/8	
Cable Type	Foam Dielectric	
Model Series	LCF78-50 Series	
Connector Interface	N	
Connector Type	ECO Series	
Sealing Method	lethod O-ring	

TESTING AND ENVIRONMENTAL

Waterproof Level	IP67
------------------	------

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	Trimetal/Silver	
Length	53mm (2.087in)	
Outer Diameter	36mm (1.417in)	
Inner Contact Attachment	Spring Finger	
Outer Contact Attachment	Spring Finger	

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms	
3rd Order IM Product @ 2x20 Watts	-155	
Maximum Frequency	5 GHz	
Frequency Range	VSWR value	Return Loss value
DC < f ≤ 1000MHz	1.1	26.4
1000 < f ≤ 2700MHz	1.13	24.3
2700 < f ≤ 3000MHz	1.15	23.1
3000 < f ≤ 5000MHz	1.3	17.7

External Document Links Notes

NM-LCF78-ECO Forstar REV : B REV DATE : 15 Nov 2025 www.rfsworld.com

Rela	ted Documents
Vela	ica Documents
D	TML Value Proposition Value Propositions

NM-LCF78-ECO_Forstar REV : B REV DATE : 15 Nov 2025 www.rfsworld.com