

**NM-SCF14-D01**

N Male Connector for 1/4" Coaxial Cable, OMNI FIT™ Premium,  
Straight, threaded gasket and 360° compression sealing



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The N connector meets all technical requirements and covers high frequencies as well as legacy applications.

Sealing against outer conductor and jacket by means of threaded gasket and 360° compression fit.

Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.;

**Feature / Benefits**

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Unique NiTin plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

**Technical features****GENERAL SPECIFICATIONS**

Cable Size	1/4
Cable Type	Foam Dielectric Superflexible
Model Series	SCF14-50 Series
Connector Interface	N
Connector Type	OMNI FIT™ PREMIUM Straight
Sealing Method	Threaded Gasket + 360° Compression

**TESTING AND ENVIRONMENTAL**

Waterproof Level	IP68
------------------	------

**MECHANICAL SPECIFICATIONS**

Plating Outer/Inner	NiTin/Silver
Length	44.6mm (1.76in)
Outer Diameter	20.2mm (0.8in)
Inner Contact Attachment	Spring Finger
Outer Contact Attachment	360° clamping




NM-SCF14-D01

N Male Connector for 1/4" Coaxial Cable, OMNI FIT™ Premium,  
Straight, threaded gasket and 360° compression sealing

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 ohms	
3rd Order IM Product @ 2x20 Watts	-156 ; typical -162	
Maximum Frequency	6.0 GHz	
Frequency Range	VSWR value	Return Loss value
0 < f ≤ 1.0 GHz	1.03	36.3
1.0 < f ≤ 2.0 GHz	1.06	30.7
2.0 < f ≤ 2.7 GHz	1.08	28.3
2.7 < f ≤ 3.7 GHz	1.12	24.9
3.7 < f ≤ 5.0 GHz	1.13	24.3
5.0 < f ≤ 6.0 GHz	1.14	23.7



External Document Links

Notes