

 ${\sf RSB\,\text{-}Clip\,Stainless\,Steel\,Hanger\,.\,\,Quantity\,of\,cable\,gripping\,tabs\,for\,the\,various\,cable\,type\,may\,be\,different.}$



Feature / Benefits

The RSB-Clip is designed for the installation of feeder cables from sizes 1/4""up to 1-5/8. The clip is a universal clamp device and can be used in many mounting configuration. The RSB-Clip is made of stainless steel. The hanger is resistant against all environmental influences. Due to the mechanical construction, a cable deformation is impossible. Therefore, a deterioration of the electrical properties is avoided.

Technical features

GENERAL SPECIFICATIONS

Product Type	Hanger	
Hanger Type	RSB-Clip	
Cable Type	Air Dielectric, Coaxial Foam Dielectric	

TESTING AND ENVIRONMENTAL

Installation Temperature	-50°C to 85°C (-58°F to 185°F)	
Operation Temperature	-50°C to 85°C (-58°F to 185°F)	
Storage Temperature	-50°C to 85°C (-58°F to 185°F)	

MECHANICAL SPECIFICATIONS

Cable Size	1-1/8
Number of Cable / Waveguide Runs	1
Material	Stainless Steel
Drill Hole Size	8mm (0.315in)

ACCESSORIES

Model Number	Description	Datasheet Link
RSB-310	Cleat	
RSB-315	Anchor bar fixation	

PACKAGING INFORMATION

Package Quantity	10

External Document Links

Notes

RSB-118 REV : B REV DATE : 15 Nov 2025 **www.rfsworld.com**