



TF320-BW1-S-120M
TwistFlex PBR/UBR320, 1.2m



Twistable and flexible rectangular waveguide R320, with PBR/UBR 320 flanges. Length = 1.2m, core with environmental impact resistant molded rubber jacket. Hardware and gasket (for PDR/PBR flanges) included.

Feature / Benefits

Waveguide installation

- The flexible and twistable rectangular waveguide component eliminates installation difficulties
- It isolates vibration
- It provides simple aid to positioning of antennas

Technical features

STRUCTURE

Type of Rectangular Waveguide Component	TwistFlex
Waveguide Size IEC (EIA)	R320 (WR28)
Flange A	PBR320
Flange B	UBR320
Flange Finish	Brass un-plated
Package Quantity	1

ELECTRICAL SPECIFICATIONS

Frequency Range	26.4 - 40.1
Attenuation	2.4 dB
Power rating	75 W

MECHANICAL SPECIFICATIONS

Maximum Twist	360m (109.7ft)
Minimum Bending Radius E-Plane	22mm (0.9in)
Minimum Bending Radius H-Plane	40mm (1.6in)
Length	1200mm (47.2in)
Weight	0.27kg (0.6lb)

MATERIAL

Material	Core: Brass silver plated Jacket: Rubber Silicone Flange: Brass
Color	Black

External Document Links

Notes